




### MAGNETIC STIRRER Model: 105







- Magnetic Stirrers are suitable for most types of laboratory applications where controlled stirring and heating is required
- Aluminum top for excellent heat distribution
- Reliable heating elements
- Temperature range 50°C 350°C, controlled by analogue potentiometer
- Reliable solid state electronic speed control
- Stirring bar 40 x 8mm
- o / RPM: 100 1800

### NOTE

• Supplied with probe stand, clamp and ceramic stirrer bar





# MAGNETIC STIRRER

Model: 105

## **SPECIFICATIONS**

 POWER
 500W

 VOLTAGE
 230V / 50Hz

 PARKAGING (W. P. II)
 230 / 310 / 315


 PACKAGING (W x D x H)
 230 x 310 x 215 (mm)


 UNIT (W x D x H)
 180 x 270 x 330 (mm)


 NET WEIGHT
 4 8 kg

 $\begin{array}{lll} \textbf{NET WEIGHT} & 4.6 \text{kg} \\ \textbf{GROSS WEIGHT} & 5 \text{kg} \\ \textbf{SHIPPING VOLUME} & 0.02 \text{m}^3 \\ \textbf{LOAD CAPACITY} & 5 \ell \end{array}$ 

RPM 100 - 1800
PLATE SIZE 170 x 170 (mm)







### NOTE

when viewing the appliance from the front in it's usual operating position, the width (W) of the product is the total distance from left to right; the depth (D) of the product is the total distance from the front to the back; the height (H) is the total distance from the bottom of the product to the top. Pictures may vary from actual product.

### **DISCLAIMER**

• Output performance figures quoted are dependant on various factors. Scientific reserves the right, without notice, to make changes and revisions to product specifications, materials and design, when we believe it will provide better performance, durability, and efficiency. Unit measurements may vary depending on point of reference.

### WARRANTY

• All Scientific equipment comes with a standard ONE year warranty, The 1 Year Extended Warranty is only valid for customers who have registered their warranty online at www.scientific.co.za within the first year after making their purchase.



www.scientific.co.za

**Published Date**: 2020.09.25